

UNIDAD DE BAJO VACIO

MODELO	RPM	50.8mm HG		101.6mm HG		152.4mm HG		203.2mm HG		254mm HG		304.8mm HG	
PESO KG.		M3/MIN.	BHP	M3/MIN.	BHP.	M3/MIN.	BHP	M3/MIN.	BHP	M3/MIN	BHP	M3/MIN.	BHP
RM-36	1760	4.5	1.1	4.1	1.9	3.8	2.8	3.6	3.6	3.3	4.5	3	5.1
40KG.	2265	5.9	1.3	5.6	2.4	5.4	3.5	5.1	4.6	4.8	5.5	4.5	6.6
	2770	7.5	1.5	7.1	2.9	6.8	4.2	6.6	5.4	6.3	6.7	6	8
	3275	8.9	1.8	8.6	3.4	8.3	5	8	6.3	7.8	7.9		
	3600	9.9	1.9	9.6	3.7			9	7	8.7	8.7	8.4	10.5
RM-48	1760	7.5	1.6	7.1	3	6.7	4.4	6.3	5.6	5.9	7	5.6	8.4
63 KG.	2190	9.6	1.9	9.1	3.7	8.8	5.2	8.4	6.9	8	8.7	7.6	10.4
	2620	11.6	2.3	11.2	4.3	10.8	6.2	10.4	8.3	10.1	10.4	9.7	12.4
	3050	13.7	2.6	13.3	5	12.9	7.2	12.5	9.7	12.2	12.1	11.8	14.5
	3600	16.3	3	15.9	15.7			15.2	11.4	14.8	14.2	14.4	17.1
RM-510	1500	13.6	2.6	13	5.1	12.5	7.3	12	9.8	11.5	12.2	10.9	14.7
115 KG.	1760	16.1	3.1	15.6	5.7	15.1	8.6	14.6	11.5	14	14.3	13.5	17.2
	2100	19.5	3.6	18.9	6.8	18.4	10.3	17.9	13.7	17.4	17.1	16.9	20.5
	2440	22.9	4.2	22.3	8	21.8	11.9	21.3	15.9	20.8	19.9	20.3	23.9
	2850	27	4.8	26.4	9.3			25.4	18.6	24.9	23.2	24.3	27.9
RM-615	1170	21.7	4.1	20.7	7.8	19.8	11.7	19.1	15.7	18.2	19.6	17.4	23.5
240 KG.	1760	33.7	5.9	32.7	11.8	31.8	17.7	31.1	23.5	30.2	29.4	29.4	35.3
	1930	37.1	6.5	36.2	12.9	35.3	19.4	34.5	25.8	33.7	32.3	32.8	38.7
	2100	40.6	7	39.6	14	38.8	21.1	37.9	28.1	37.2	35.1	36.3	42.1
	2350	45.7	7.9	44.7	15.7			43.1	31.4	42.2	39.3	41.4	47.1
RM-718	1170	37.1	6.5	35.9	13.1	34.8	19.6	33.8	26.2	32.8	32.7	31.7	39.2
360 KG.	1465	47.2	8.2	45.9	16.4	44.9	24.6	43.9	32.8	42.8	40.9	41.8	49.1
	1760	57.2	9.8	55.9	19.7	54.9	29.5	53.9	39.3	52.9	49.2	51.8	59
	1800	58.5	10.1	57.3	20.1	56.2	30.2	55.3	40.2	54.2	50.3	53.2	60.4
	2050	67	11.5	65.8	22.9			63.7	45.8	62.7	57.3	61.6	68.7
RM-820	880	39.9	7.1	38.4	14.3	37	21.4	35.7	28.5	34.4	35.7	32.9	42.8
570 KG.	1170	54.2	9.5	52.6	19	51.3	28.4	50	37.9	48.7	47.4	47.3	56.9
	1375	64.3	11.1	62.8	22.3	61.4	33.4	60.1	44.6	58.8	55.7	57.4	66.9
	1575	74.2	12.8	72.6	25.5	71.3	38.3	69.9	51.1	68.6	63.8	67.2	76.6
	1800	85.3	14.6	83.7	29.2			81	58.3	79.7	72.9	78.3	87.5