

MODELO	PESO KG.	RPM	50.8mm HG		101.6mm HG		152.4mm HG		203.2mm HG		254mm HG		304.8mm HG		355.6mm HG	
			M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP
RM-36 40 KG.	1760	4.5	1.1	4.1	1.9	3.8	2.8	3.6	3.6	3.3	4.5	3.0	5.1			
	2265	5.9	1.3	5.6	2.4	5.4	3.5	5.1	4.6	4.8	5.5	4.5	6.6			
	2770	7.5	1.5	7.1	2.9	6.8	4.2	6.6	5.4	6.3	6.7	6.0	8.0			
	3275	8.9	1.8	8.6	3.4	8.3	5.0	8.0	6.3	7.8	7.9					
	3600	9.9	1.9	9.6	3.7			9.0	7.0	8.7	8.7	8.4	10.5	8.16	12.2	
RM-48 63 KG.	1760	7.5	1.6	7.1	3.0	6.7	4.4	6.3	5.6	5.9	7.0	5.6	8.4			
	2190	9.6	1.9	9.1	3.7	8.8	5.2	8.4	6.9	8.0	8.7	7.6	10.4			
	2620	11.6	2.3	11.2	4.3	10.8	6.2	10.4	8.3	10.1	10.4	9.7	12.4	9.32	14.5	
	3050	13.7	2.6	13.3	5.0	12.9	7.2	12.5	9.7	12.2	12.1	11.8	14.5	14.02	20.0	
	3600	16.3	3.0	15.9	15.7			15.2	11.4	14.8	14.2	14.4	17.1			
RM-510 115 KG.	1500	13.6	2.6	13.0	5.1	12.5	7.3	12.0	9.8	11.5	12.2	10.9	14.7			
	1760	16.1	3.1	15.6	5.7	15.1	8.6	14.6	11.5	14.0	14.3	13.5	17.2	13.0	20.1	
	2100	19.5	3.6	18.9	6.8	18.4	10.3	17.9	13.7	17.4	17.1	16.9	20.5	16.37	24.0	
	2440	22.9	4.2	22.3	8.0	21.8	11.9	21.3	15.9	20.8	19.9	20.3	23.9			
	2850	27.0	4.8	26.4	9.3			25.4	18.6	24.9	23.2	24.3	27.9	23.79	32.5	
RM-615 240 KG.	1170	21.7	4.1	20.7	7.8	19.8	11.7	19.1	15.7	18.2	19.6	17.4	23.5			
	1760	33.7	5.9	32.7	11.8	31.8	17.7	31.1	23.5	30.2	29.4	29.4	35.3	28.46	41.2	
	1930	37.1	6.5	36.2	12.9	35.3	19.4	34.5	25.8	33.7	32.3	32.8	38.7	31.91	45.2	
	2100	40.6	7.0	39.6	14.0	38.8	21.1	37.9	28.1	37.2	35.1	36.3	42.1			
	2350	45.7	7.9	44.7	15.7			43.1	31.4	42.2	39.3	41.4	47.1	40.46	55.0	
RM-718 360 KG.	1170	37.1	6.5	35.9	13.1	34.8	19.6	33.8	26.2	32.8	32.7	31.7	39.2			
	1465	47.2	8.2	45.9	16.4	44.9	24.6	43.9	32.8	42.8	40.9	41.8	49.1			
	1760	57.2	9.8	55.9	19.7	54.9	29.5	53.9	39.3	52.9	49.2	51.8	59.0			
	1800	58.5	10.1	57.3	20.1	56.2	30.2	55.3	40.2	54.2	50.3	53.2	60.4			
	2050	67.0	11.5	65.8	22.9			63.7	45.8	62.7	57.3	61.6	68.7			
RM-820 570 KG.	880	39.9	7.1	38.4	14.3	37.0	21.4	35.7	28.5	34.4	35.7	32.9	42.8			
	1170	54.2	9.5	52.6	19.0	51.3	28.4	50.0	37.9	48.7	47.4	47.3	56.9			
	1375	64.3	11.1	62.8	22.3	61.4	33.4	60.1	44.6	58.8	55.7	57.4	66.9			
	1575	74.2	12.8	72.6	25.5	71.3	38.3	69.9	51.1	68.6	63.8	67.2	76.6			
	1800	85.3	14.6	83.7	29.2			81.0	58.3	79.7	72.9	78.3	87.5			

UNIDAD DE MEDIO VACÍO	MODELO	RPM	152.4mm HG		203.2mm HG		254mm HG		304.8mm HG		355.6mm HG		381mm HG		406.4 HG	
	PESO KG.		M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP
RM-33 35 KG.	1760	2.1	1.6	1.9	2.1	1.8	2.6	1.6	3.1							
	2265	3.0	2.0	2.8	2.6	2.6	3.3	2.4	3.9							
	2770	3.8	2.4	3.7	3.2	3.5	4.0	3.3	4.7	3.1	5.4					
	3275	4.7	2.8	4.5	3.8	4.3	4.7	4.2	5.5	3.9	6.4					
	3600	5.3	3.1			4.9	5.0	4.7	6.0	4.5	7.0	4.4	7.5			
RM-45 52 KG.	1760	4.5	3.0	4.3	3.9	4.0	4.8	3.7	5.8							
	2190	5.9	3.7	5.7	4.8	5.4	6.0	5.2	7.2							
	2620	7.4	4.4	7.1	5.7	6.9	7.1	6.6	8.6	6.3	10.0					
	3050	8.8	5.1	8.6	6.6	8.3	8.3	8.0	10.0	7.7	11.6					
	3600	10.6	5.9			10.1	9.8	9.8	11.8	9.5	13.7	9.4	14.7	9.2	15.7	
RM-56 85 KG.	1500	7.3	4.5	7.0	5.9	6.6	7.3	6.3	8.8	5.9	10.3					
	1760	8.8	5.2	8.5	6.9	8.2	8.6	7.8	10.3	7.4	12.1					
	2100	10.9	6.2	10.5	8.2	10.2	10.3	9.9	12.3	9.5	14.4	9.2	15.4			
	2440	12.9	7.2	12.6	9.5	12.3	11.9	11.9	14.3	11.5	16.7					
	2850	15.3	8.4			14.7	13.9	14.3	16.7	13.9	19.5	13.7	20.9	13.5	22.3	
RM-68 175 KG.	1170	10.3	6.3	9.8	8.3	9.3	10.4	8.8	12.5	8.2	14.6	7.8	15.6	7.5	16.7	
	1760	16.7	9.4	16.2	12.6	15.7	15.7	15.2	18.8	14.6	22.0	14.2	23.5	13.9	25.1	
	1930	18.5	10.3	18.0	13.8	17.5	17.2	17.0	20.7	16.4	24.1	16.1	25.8	15.8	27.5	
	2100	20.4	11.2	19.8	15.0	19.4	18.7	18.8	22.5	18.3	26.2			17.6	30.0	
	2350	23.0	12.6			22.0	21.0	21.6	25.1	20.1	29.3	20.7	31.4	20.3	33.5	
RM-711 300 KG.	1170	20.9	12.0	20.2	16.0	19.5	20.0	18.7	24.0	17.9	28.0	17.4	30.0	17.0	32.0	
	1465	27.0	15.0	26.3	20.0	25.6	25.0	24.8	30.0	24.1	35.0	23.6	37.5	23.2	40.0	
	1760	33.1	18.0	32.4	24.0	31.7	30.0	31.0	36.1	30.2	42.1	29.7	45.1	29.3	48.1	
	1800	33.9	18.4	33.3	24.6	32.6	30.7	31.8	36.9	31.0	43.0			30.1	49.2	
	2050	39.2	21.0			37.7	35.0	37.0	42.0	36.2	49.0	35.7	52.5	35.3	56.0	
RM-812 450 KG.	880	21.6	12.8	20.8	17.1	19.9	21.3	18.9	25.6	18.0	29.8	17.3	32.0	16.8	34.1	
	1170	30.2	17.0	29.3	22.7	28.4	28.3	27.5	34.0	26.5	39.7	25.9	42.5	25.4	45.3	
	1375	36.2	20.0	35.4	26.6	34.5	33.3	33.5	40.0	32.5	46.6	31.9	49.9	31.4	53.3	
	1575	42.1	22.9	41.2	30.5	40.4	38.1	39.4	45.8	38.4	53.4			37.3	61.0	
	1800	48.8	26.2			47.0	43.6	46.1	52.3	45.0	61.0	44.5	65.4	43.8	69.7	

UNIDAD DE ALTO VACÍO	MODELO	RPM	152.4mm HG		203.2mm HG		254mm HG		304.8mm HG		355.6mm HG		381mm HG		406.4 HG	
	PESO		M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	BHP	M3/ MIN	
RM-32 30 KG.	1760	1.5	1.3	1.4	1.7	1.3	1.8	1.1	2.4							
	2265	2.2	1.6	2	2.1	1.9	2.4	1.7	3.0							
	2770	2.8	1.9	2.7	2.5	2.5	2.9	2.4	3.7	2.2	4.3	2.1	4.6			
	3275	3.5	2.1	3.3	2.7	3.2	3.4	3.0	4.1	2.9	4.8					
	3600	3.9	2.5	3.8	3.2			3.4	4.7	3.3	5.3	3.2	5.7	3.1	6.0	
RM-43 45 KG.	1760	2.6	1.9	2.4	2.5	2.2	2.8	2.0	3.6							
	2190	3.4	2.3	3.2	3	3.1	3.5	2.9	4.4	2.7	5.1	2.6	5.3			
	2620	4.3	2.7	4.1	3.6	3.9	4.2	3.7	5.1	3.5	5.9	3.4	6.3			
	3050	5.1	2.9	4.9	3.9	4.7	4.9	4.5	5.9	4.4	6.9					
	3600	6.2	3.7	6.0	4.8			5.6	6.9	5.4	8.1	5.3	8.7	5.2	9.3	
RM-54 88 KG.	1500	4.8	3.1	4.5	4.1	4.3	4.9	4.1	5.9	3.8	6.8					
	1760	5.8	3.6	5.6	4.8	5.3	5.7	5.1	6.9	4.8	8.0	4.7	8.6			
	2100	7.2	4.3	6.9	5.5	6.7	6.8	6.4	8.2	6.2	9.6	6.0	10.3			
	2440	8.5	4.8	8.3	6.4	8.1	8.0	7.8	9.5	7.5	11.1					
	2850	10.1	5.6	9.9	7.4			9.4	11.1	9.1	13.0	9.0	13.9	8.8	14.9	
RM-64 160 KG.	1170	5.9	3.9	5.6	5.1	5.2	6.2	4.9	7.4	4.5	8.7	4.3	9.3			
	1760	9.7	5.6	9.4	7.4	9.0	9.3	8.7	11.2	8.3	13.0	8.1	14.0	7.8	14.9	
	1930	10.8	6.1	10.5	8.2	10.1	10.2	9.8	12.2	9.4	14.3	9.2	15.3	8.9	16.3	
	2100	11.9	6.7	11.5	8.9	11.2	11.1	10.8	13.3	10.5	15.5			10.0	17.8	
	2350	13.5	7.5	13.2	9.9			12.5	14.9	12.1	17.4	11.8	18.6	11.7	19.9	
RM-75 235 KG.	1170	10.2	6.0	9.7	8.0	9.3	10.0	8.9	12.0	8.4	14.0	8.1	15.0	7.9	16.0	
	1465	13.2	7.5	12.8	10.0	12.4	12.5	11.9	15.0	11.5	17.5	11.2	18.8	10.9	20.0	
	1760	16.3	9.0	15.9	12.0	15.4	15.0	15.0	18.1	14.5	21.1	14.3	22.6	14.0	24.1	
	1800	16.7	9.2	16.3	12.3	15.9	15.4	15.4	18.5	14.9	21.5			14.4	24.6	
	2050	19.3	10.5	18.9	14.0			18.0	21.0	17.5	24.5	17.3	26.3	17.0	28.0	
RM-86 370 KG.	880	11.3	7.0	10.7	9.3	10.2	11.6	9.6	13.9	8.9	16.2	8.5	17.4			
	1170	15.9	9.3	15.4	12.3	14.8	15.4	14.2	18.5	13.6	21.6	13.2	23.1	12.8	24.7	
	1375	19.2	10.9	18.7	14.5	18.1	18.1	17.5	21.7	16.8	25.4	16.5	27.2	16.1	29.0	
	1575	22.5	12.5	21.9	16.6	21.3	20.8	20.7	24.9	20.0	29.1			19.3	33.2	
	1800	26.0	14.2	25.5	19.0			24.3	28.5	23.6	33.2	23.3	35.6	22.9	38.0	

Las capacidades y la potencia están basadas en vacío a la succión y a la descarga en condiciones normales.